

# BranchFormation

Monimax 5600

The compact **Monimax 5600** ensures optimal deployment flexibility, and is therefore appropriate for in-branch or off-premise installations. Furthermore, the **5600** delivers unsurpassed reliability, security and high capacity.



## TRANSFORM YOUR BANK BRANCHES WITH BRANCHSERV

### Superior, Flexible Design

The **5600** boasts one of the most efficient user interfaces available - 10% to 40% more compact than most competitors. The **5600** also offers a full range of advertising and marketing support along with a five high option for the dispenser. An industry standard 15.1" TFT may be complemented with an optional, vacuum florescent display (VFD) for unparalleled visibility.

### Security

The **5600's** UL-291 Level 1-rated safe has been proven both in the field and in independent third party attack tests. The latter confirmed the fact that it indeed exceeds UL rating requirements. Enhanced security options are also available, including market leading software, transactional security features and video surveillance cameras.

### Dependability

The **5600** is the ideal self-service platform for transaction intensive branches or off-premise deployments. And it is designed to ensure reliability that supports high uptime delivery.

## System Control

- Intel® processor
- Microsoft® Windows® 7 platform
- NDC+, User Application

## Communication

- TCP/IP

## Customer Display

- 15" color TFT LCD
- Sunlight readable w/ touch screen

### Optional

- Privacy filter
- Touch screen

## Input Type

- 4 x 2 function keys (option)
- PCI EPP (encrypting PIN pad)
- ADA compliant

## Card Handling

- Dip-type card reader
- ### Optional
- Anti-skimming

## Cash Dispensing

- 3,000 notes cassette (up to 5 cassettes)
- Bundle retraction
- Automatic shutter

## Printers

- 3.1" graphic thermal receipt printer
- Electronic journal
- 5,000 transactions

## Security

- UL291 Level-1 safe
  - Electronic safe lock
- ### Optional
- KABA Mas Cencon safe lock
  - Security cameras

## Miscellaneous

- Lead-through indicator
- ### Optional
- VFD (Vacuum Fluorescent Display)

## Power Supply

- AC 110-240 V, 50-60 Hz
- Backup battery

## Operating Environment

- Temperature: 0°C - 40°C (31°F - 104°F)

### Optional

- Humidity: 25% - 85%

## Dimensions

- Height: 59.3" (1,505mm)
- Width: 18.5" (470mm)
- Depth: 29.9" (760mm)
- Weight: 1093lbs. (495kg) (Level 1 safe)

*Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.*

